



701 SELF-LOADING WRECKER



SPECIFICATIONS

- Wheel Lift Fully Extended 5,000 lbs
- Maximum Underlift Reach 75"
- 7,500 lb Tow Rating
- Recovery Boom at Boom Head Swivel 10,000 lbs

All Ratings are based on structural factors only, not vehicle capacities or capabilities. Specifications shown are approximations and may vary depending on chassis selected. Dynamic Towing reserves the right to change or modify product and or specifications without notice or obligation. Some equipment shown is optional.

STANDARD FEATURES

- 5,000 lb Self-Loading Wheel Lift
- In Cab Wheel Lift Controls
- 60" Cab to Axel All Steel Body
- Safety Chains, Straps & Ratchets
- FMVSS 108 LED Light Group
- 88" to 91" Body Width
- Tire Spacer Blocks
- Bronze Bushings
- Reese Hitch
- Steel Pylon

OPTIONAL FEATURES

- Lightning Body
- 8,000 lb Drag Winch with 100 ft 3/8 cable
- Stainless Steel Pylon
- Diamond Plate Dress Up Package
- Side Load Tool Boxes
- Motorcycle Attachment

CHASSIS RECOMMENDATIONS

- Minimum Cab to Axel 60"
- Max. Cab to Axel Tunnel Box 84"
- Suggested GVWR 11,500 lbs

LIKE US ON FACEBOOK



WWW.DYNAMICTOW.COM

CONTACT US: 1-800-831-9299